

# NLS-EM20-85 Series

## OEM Scan Engine



### Features

#### ■ UIMG® Technology

Armed with Newland's six-generation of **UIMG®** technology, the scan engine can swiftly and effortlessly decode even poor quality barcodes.

#### ■ Snappy On-Screen and Printed Barcode Capture

The NLS-EM20-85 excels at reading on-screen barcodes even when the screen is covered with protective film or set to its lowest brightness level. Besides, it achieves optimal performance in reading commodity barcodes with various materials and printed barcodes.

#### ■ Ultra-Compact Size

At less than 2.0cm, the slim footprint makes this scan engine easier to fit into super-thin devices.

#### ■ Optional Functions

The NLS-EM20-85 with glass or foam provides the NFC or non-NFC function, which greatly satisfies different demands. It supports access card, user card, membership card, etc.

#### ■ Multiple Interfaces

The NLS-EM20-85 supports USB, RS-232 and TTL-232 interfaces to meet diverse customer needs.

### Application Scenarios (as an accessory)

Retail desktop, vertical and wall-mounted terminals, self-service cabinets used in e-commerce and smart homes, information verification terminals, etc.

# NLS-EM20-85 Series

## OEM Scan Engine

SCANNING MADE SIMPLE

<b>Performance</b>	Image Sensor		640 * 480 CMOS	
	Illumination		White LED	
	Symbologies	2D	PDF417, Micro PDF417, QR, Micro QR, Data Matrix, Aztec, Maxicode	
		1D	Code 128, UCC/EAN-128, AIM 128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Standard 25, Codabar, Industrial 25, Code 39, Code 93, Code 11, Plessey, MSI-Plessey, GS1-128 (UCC/EAN-128), GS1-DataBar™ (RSS) (RSS-14, RSS-Limited, RSS-Expand), Matrix 2 of 5	
	Resolution*		≥5mil (1D)	
	Typical Depth of Field*	EAN-13	30mm-85mm (13mil)	QR Code 15mm-75mm (15mil)
		PDF417	30mm-50mm (6.7mil)	Code 39 25mm-70mm (5mil)
		Data Matrix	25mm-60mm (10mil)	
	Min. Symbol Contrast*		25%	
	Scan Angle**		Roll: 360°, Pitch: ±60°, Skew: ±60°	
	Motion Tolerance*		1.5m/s	
	Field of View		Horizontal 68°, Vertical 51°	
	NFC Function (Only for NFC version)		Available	
	Reading Distance of NFC Card (Only for NFC version)		0-40mm (typical)	
	NFC Card Type (Only for NFC version)		See NFC Card Type Available for the NLS-EM20-85	
<b>Mechanical/ Electrical</b>	Interface		TTL-232, RS-232, USB	
	Operating Voltage		5VDC±5%	
	Rated Power Consumption@5VDC		1.07W (Non-NFC)	1.26W (NFC)
	Current@5VDC	Operating	215mA (typical), 578mA (max.) (Non-NFC) 253mA (typical), 736mA (max.) (NFC)	
		Standby	120mA (Non-NFC)	144mA (NFC)
	Dimensions	With Foam	61.5 (W)×65.5 (D)×18.8 (H)mm (max.)	
		With Glass	61.5 (W)×65.5 (D)×18.3 (H)mm (max.)	
	Weight		27.4g (with foam)	36.4g (with glass)
<b>Environmental</b>	Notification		Beeper	
	Operating Temperature		-20°C to 60°C (-4°F to 140°F)	
	Storage Temperature		-40°C to 70°C (-40°F to 158°F)	
	Humidity		5% to 95% (non-condensing)	
<b>Certifications</b>	Ambient Light		0~100,000lux (natural light)	
			FCC Part 15 Class B, CE EMC Class B, RoHS	
<b>Accessories</b>	Cable	USB	Used to connect the engine to a host device.	
		RS-232	Used to connect the engine to a host device.	
		FFC Cable	Used to connect the NLS-EVK to a host device.	

\*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland (1D EAN-13 sample printed barcode for motion tolerance);

\*\*Test conditions: Scan Distance=(min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

2D: Printed QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version: V1.1

### Newland Headquarter

Add: NO.1 Rujiang West Rd.,  
Mawei, Fuzhou, Fujian 350015, China  
Tel: +86 591 8397 9500  
Email: info@nlscan.com  
Web: www.newlandaidc.com

### Newland APAC

**Taiwan** Tel: +886 2 7731 5388  
Taiwan Email: info@newland-id.com.tw  
Web: www.newland-id.com.tw  
**Japan** Tel: +886 2 7731 5388 ext. 71  
**Korea** Tel: +82 10 8990 4838  
**India** Tel: +91 120 7964266  
Japan/Korea/India Email: info@nlscan.com  
Web: www.newlandaidc.com

### Newland NALA

**North America** Tel: +1 510 490 3888  
North America Email: info@nlscan.com  
**Latin America** Tel: +1 239 598 0068  
Latin America Email: info@newlandla.com  
Web: www.newlandamerica.com

### Newland EMEA

Tel: +31 (0) 345 87 00 33  
Email: sales@newland-id.com  
Tech Support: tech-support@newland-id.com  
Web: www.newland-id.com

