

NLS-HR1070

Hand-held Barcode Scanner

- ◆ Ergonomic Lightweight Design
- **♦ Cost-effective Solution**
- ◆ Snappy Scanning Performance



Features

■ Ergonomic Lightweight Design

This ergonomic lightweight scanner fits comfortably in any user's hands to reduce the fatigue of long-time operation, ideally suited for scan-intensive applications.

■ Cost-effective Solution

The NLS-HR1070 delivers aggressive scanning capabilities and excellent user experiences at an attractive price.

■ Snappy Scanning Performance

The NLS-HR1070 offers an impressive read rate of up to 300 scans per second, helping boost productivity and profitability.

Application Scenarios

Retail chains, inventory counting, express delivery services, warehouse management, food traceability, healthcare, manufacturing, electricity meter reading.

NLS-HR1070

Hand-held Barcode Scanner

SEANNING MADE SIMPLE

Performance	Image Sensor		Linear imager
	Light Source		Red LED (610nm~640nm)
	Symbologies		EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar,
			Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 25
			Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11,
			MSI-Plessey, Plessey.
	Resolution		≥5mil
	Typical Depth of Field	EAN-13	50mm-480mm (13mil)
		Code 39	50mm-180mm (5mil)
	Scan Angle	Pitch	±60°@ 0°Roll and 0° Skew
		Roll	±30°@ 0°Pitch and 0° Skew
		Skew	±60°@ 0°Roll and 0° Pitch
	Symbol Contrast		≥30%
	Scan Rate		300 scans per second
	Interface		USB
Physical/	Dimensions (L×W×H)		160×95×65mm
Electrical	Weight		220g (USB cable included)
	Notification		Beep, LED indicator
	Input Voltage		DC5V
	Current	Maximum	<130mA
		Operating	60mA±10mA
		Standby	15mA±5mA
Environmental	Operating Temperature		-20°C~+60°C
	Storage Temperature		-40°C~+85°C
	Humidity		5%~95% (non-condensing)

^{*}Specifications are subject to change without notice.*

Version: V1.0

