

S1 Series

Standing Advertising Player Machine



FMT S1 Series

All-in-one professional display device that integrates query, interaction and information release. The appearance, internal structure and functional design are all built for commercial use. It has a variety of appearance structures and can be customized. It is widely used in public information inquiries in various industries.

Highlight

- Scratch-resistant and wear-resistant , Dust-proof and waterproof
- Professional chip and processing technology with high picture quality
- Industrial-grade high-performance LCD screen to ensure high-definition , high-brightness and stability of images
- Shell is designed with high-strength steel
- Appearance is ultra-thin, beautiful and strong, with excellent protection level and electromagnetic shielding performance
- Surface has fine grained paint, smooth and uniform, simple and generous,
- Machine color is integrated with the industrial host , and has a good anti-rust and wear-resistant
- Multiple signal interfaces, support multiple signal input/output
- High reliability, high stability, suitable for education and training, exhibitions, public media, video conferences, military command, traffic management
- Industrial grade motherboards



Configuration

Standard Configuration

- Android 7.1 RK3288
- Cortex-A17 quad-core CPU Mali-T764 1.8 Ghz
- 2GB RAM / 16GB ROM EMMC Storage

Configuration option-1

- Android 9.0 RK3399
- Quad-core 64-bit high-performance CPU 2.0Ghz
- 2GB RAM / 16GB ROM EMMC Storage

CPU Option

- Dual-core Cortex-A72,
- Quad-core Cortex A-53 64-bit
- Quad-core arm Mali-T860MP4 High-performance CPU

Other Option

- Ram 4 GB, Rom 32/64 GB
- Built-in low power consumption MCU Cortex-M0
- Wireless WiFi (Mini-PCIe 4G optional)

Color Available



Black

White

Silver

Color can be customize specification and function, etc. Welcome to consult.

S1 Series

Standing Advertising Player Machine



Application

- Sales hall, real estate agency (house type and landscape effect display)
- Car for sale shop (car model display)
- Furniture and art store (product display)
- Cinema (movie trailer and clip appreciation)
- Office building and apartment lobby (advertising)
- Banks and other financial institutions
 - business inquiries
 - service promotion
- Telecommunications
- Government agencies (public information release, government affairs disclosure)
- Shopping center (shopping guide, merchant and product inquiry, advertising promotion)
- Fashion flagship store, specialty store (new product introduction)
- Company reception room or meeting room (company introduction, exhibit display)
- Exhibition hall and venue design company (event venue layout)

Introduction to network version features

- Perfect support for 1080P full HD decoding, compatible to drive 15-100 inch LCD screen.
- Support mainstream media formats, support split-screen playback functions such as pictures, videos, rolling subtitles, and office software.
- Support display of station logo, date, time, week, weather forecast, etc.
- Diverse and flexible interface layout, split screen and full screen freely.
- Any switch between horizontal and vertical screens, smooth transition without black screen.
- Support picture + background music playback mode, which can replace traditional light boxes and posters.
- Support multiple playback modes such as loop, timing, interstitial, pad, etc., to achieve flexible control of playback time, sequence, frequency, content, location, etc.
- Multi-screen interaction, realizing multiple display terminals to play the same content at the same time.
- Support resumable downloading and downloading regularly, and reasonably occupy network bandwidth.
- Super multi-period timing switch function, unattended.
- Support U disk import or direct playback.
- Automatic repair, remote upgrade, intelligent domain name resolution, convenient and quick operation and maintenance
- Support LAN/WiFi/3G/4G network access, which can realize multi-network hybrid networking.

Digital Signage **S1 Series**
Standing Advertising Player Machine


FMT Corporation Co., Ltd.

Leading Business Automatic Machine
49/293 Soi Vibhavadi-Rangsit 64 Yeak 13,
Talat Bangkhen, Lak Si,
Bangkok 10210
02-5217155-59
086-6889050
fmt_sales@hotmail.com



S1 Series

Standing Advertising Player Machine



	FM-43S1NT	FM-49S1NT	FM-55S1NT	FM-65S1NT
Model :	43 inch	49 inch	55 inch	65 inch
Machine size :	1800 x 600 x 450 mm.	1850 x 672 x 450 mm.	1900 x 756 x 500 mm.	2100 x 882 x 500 mm.
Screen size:	941 x 530 mm.	1076 x 607 mm.	1209 x 680 mm.	1428 x 805 mm.
Carton size :	1900 x 200 x 720 mm.	1930 x 200 x 700 mm.	1980 x 200 x 880 mm.	2200 x 200 x 1050 mm.
Weight :	60 Kg.	65 Kg.	70 Kg.	80 Kg.
LED Parameter				
LED Brand :	43 inch (LG/BOE)	49 inch (LG/BOE)	55 inch (LG/BOE)	65 inch (LG/BOE)
Display ratio :	16 : 9	16 : 9	16 : 9	16 : 9
Resolution :	1920 x 1080 / 3840 x 2160	1920 x 1080 / 3840 x 2160	1920 x 1080 / 3840 x 2160	1920 x 1080 / 3840 x 2160
Pixel pitch :	0.1815 x 0.5415 mm	0.1815 x 0.5415 mm	0.1815 x 0.5415 mm	0.1815 x 0.5415 mm
Horizontal frequency :	30-80 KHz.	30-80 KHz.	30-80 KHz.	30-80 KHz.
Vertical frequency :	60 / 75 Hz.	60 / 75 Hz.	60 / 75 Hz.	60 / 75 Hz.
Color support :	16.77 million	16.77 million	16.77 million	16.77 million
LED Life :	50,000 Hrs.	50,000 Hrs.	50,000 Hrs.	50,000 Hrs.
Average brightness :	350 cd/m ²	350 cd/m ²	500 cd/m ²	500 cd/m ²
Contrass :	1200 : 1	1200 : 1	1200 : 1	1200 : 1
Viewing angle :	Up/Down/Left/Right 178°	Up/Down/Left/Right 178°	Up/Down/Left/Right 178°	Up/Down/Left/Right 178°
Input voltage :	110-220 VAC (50-60 Hz)	110-220 VAC (50-60 Hz)	110-220 VAC (50-60 Hz)	110-220 VAC (50-60 Hz)
Power management :	Compliant with VESA DPMS	Compliant with VESA DPMS	Compliant with VESA DPMS	Compliant with VESA DPMS
Power consumption :	< 110W	< 110W	< 110W	< 110W
Working temperature :	0 - 40 °C	0 - 40 °C	0 - 40 °C	0 - 40 °C
Storage temperature :	-10 - 50 °C	-10 - 50 °C	-10 - 50 °C	-10 - 50 °C
TV Parameters (optional)				
TV system :	NTSC M/N , PAL BG/DK/11/H , SECAM L/L			
Resolution :	Analog and digital support upto 1080P format			
Input interface :	TV , VGA , HDMI , YPBPR , USB , AV , S-VIDEO			
Output interface :	AV			
Voice control :	Automatic sound standard detection, support balance adjustment, surround			
Sound power :	2 x 10 W			
Input/output ports (optional)				
USB Interface :	2 x USB 2.0			
TF Card :	Standard 1 channel, multiple channels can be customize			
HDMI Interface :	1			
DC :	1			
MIC audio input :	1			
LINE audio output interface :	1			
LAN network interface :	1			
Power				
Voltage :	DC 12V / AC 100-240V 50-60 Hz (External)			
Standby power (Energy Star) :	1W			
Configuration option				
Standard configuration :	J1900 industrial control motherboard , CPU Celeron quad-core 1.8 GHz , Memory and harddisk optional			
Hi-end configuration :	H81 / B75 industrial control motherboard , CPU G2030/I3/I5/I7 , Memory and harddisk optional			
Power supply :	Megmeet integrated power supply			
Wireless keyboard and mouse :	Optional			
Strage humidity :	5% - 95%			



KEY



Wi-Fi Antenna




Power cable



Hex Wrench



Warranty Card



QC Sticker

Digital Signage S1 Series
Standing Advertising Player Machine

FMT Corporation Co.,Ltd.

Leading Business Automatic Machine
49/293 Soi Vibhavadi-Rangsit 64 Yeak 13,
Talat Bangkhen, Lak Si,
Bangkok 10210
02-5217155-59
086-6889050
fmt_sales@hotmail.com

