

F-201 / F-201K

2 inch panel mounted thermal printer



F-201 / F-201K

2 inch panel mounted thermal printer

F-201 : roll bucket opening by pressing button

F-201K : roll bucket opening by pulgging in key

Feature

- Brand name printer mechanism and auto cutter
- Patented printer roll bucket opening method
- Big roll diameter Ø 56 mm
- Compact footprint
- Available customized shell color

Application

Queue management system, Visitor attendance terminal, Ticket vendor, POS, Medical instrument, Gas pump station, PC panel and control systems, Payment kiosk and more...



Black

White



58 mm.



100 mm./s



384 D/L



Autocut



Model : F-201 / F-201K Specification

Mechanism

Printing Method	Thermal dot line
Dot / Line	384 dot/line
Resolution	8 dot / mm
Printing Speed	100 mm/s
Paper width	58 mm
Printing width	48 mm
Paper roll diameter (max)	56 mm
Paper thickness	60-80 Micron
Paper loading method	Easy loading
Auto cutting	YES / Full-Partial by command

Sensor

Printer Head	Thermistor
Paper end	Photo-interrupter

Power feature

Working coltage (Vp)	12-24 VDC
Power consumption	2A (average)
Peal current	4A

Environment

Working temperature	-10 ~ 60 °C
Working humidity	20 ~ 85 %RH
Storage Temperature	-20 ~ 60 °C
Storage humidity	10 ~ 90 %RH

Reliability

Cutter life	up to 1,200,000 cuts (Depend on paper thickness)
Pulse	100,000,000
Printing length	up to 1,500,000 m (150 km)

Property

Dimension	101 x 56 x 100	
Weight	FPT-201 : 250 g	FPT-201K : 270 g

Support

Interface	USB or RS-232C
Command	ESC / POS
Driver	Windows / Linux / Android / Rasberry Pi

FMT Coraporation Co.,Ltd.

49/293 Soi Vibhavadi-Rangsit 64 Yeak 13,
Talat Bangkhen, Lak Si, Bangkok 10210 Thailand
Tel 662-5218155-59, Fax 662-5217156-7

Website : www.fmtcorp.co.th, E-mail : fmt_sales@hotmail.com

