

Thermal Receipt Printer

F-5890K



- USB / USB + Bluetooth
- Suitable for all types of commercial detail POS systems
- Light in weight and smart in shape
- High-quality printing and low cost
- Low noise and high-speed printing
- Support cash drawer driver
- Built-in power supply



F-5890K

Thermal Receipt Printer



Specification

Print Command	ESC/POS
Print Method	Thermal Line Printing
Print Speed	70mm/s
Resolution	203DPI (8dot/mm)
No. of Total Dots	384 dots/Line
Print Width	48mm
Character Size	1.5 x 3.0mm (W x H)/3.0 x 3.0mm (W x H)
Print Font	12 x 24; 24x 24
Character Set	Alphanumeric /Chinese Kanji
Data Buffer	UP to 20K bytes
Compatible OS	Window Systems; Linux Operate Systems
Interface	USB / USB+Bluetooth

Paper

Type	Roll Paper
Width	58.0±0.1mm
Roll Diameter	φ≤50mm
Paper Thickness	0.06-0.08mm

Electrical

Adapter Voltage	DC 9V/3A
Cash Drawer Control	DC 12V/1A
Print Head	Reliability
Print Reliability	100km

Physical

Dimension	17.5*13*11(cm)
Unit Weight	0.85kg (including accessories: manual, cable, test paper)
Color	Black, white
Pieces Per CTN	18pieces
CTN Dimension	49*42*40(cm)
Carton Weight	16kg

Environmental

Temperature	Working: 0 to 45 Degrees
Humidity	Working: 10%-80%
Warranty	12 months at least
Certificates	CE& FCC ROHS / ISO9001:2008