

F-9200

Bluetooth Thermal Printer

- Connectivity USB / Lan / Bluetooth
- Print Speed 160 mm./s
- Thermal print system no need ink ribbon
- Programming language CPCL / TSPL
- Double body structure for heavy duty use
- Include roll/fold paper tray
- Paper width 110 mm.
- Easy install and easy setting



Specification

Interface Selection	1. USB only / 2. USB and LAN / 3. USB and Bluetooth
Program Language	CPCL / TSPL (ESP/POS) Command
Print System	Direct Line Thermal Print
Print Speed	160 mm./s
Resolution	203 Dpi
Font Support	11 Types of Font
Image	Support Logo/Trademark
Media Sensor	Transmissive and Reflective Sensor
1D Barcode	UPC-A / UPC-E / JAN13 / EAN13 / JAN8 / EAN8 CODE39 / ITF / CODEBAR / CODE93 / CODE128
2D QR-CODE	QR-Code , PDF417
Printer Driver	Windows 2003 / XP / 7 / 8 / 10 / MAC / IOS / Android
Paper Type	Roll Paper / Label / Fold Label / Tag Paper
Effective Print Width	100 mm. (80 Point Max)
Paper Width	110 mm.
Paper Thickness	0.06 - 0.30 mm.
Charger	External Charger 24 VDC / 2.5 A
Print Reliability	upto 50,000 m.
Dimension	180 x 115 x 107 mm.
Unit Weight	2.5 Kg. (Include Accessories)
Carton Pack	8 Pcs.
Carton Dimension	40 x 37.5 x 40 cm.
Gross Weight	22 Kg.
Printer Color	White
Operate Temp	0 - 50 °C (No Condensation)
Operated Humidity	20% - 85% RH
Storage Temp	-20 - 60 °C
Storage Humidity	5% - 95% (No Condensation)
Print Noise	< 60dB

